

Personal Sound Amplifier

HANDHELD SOUND AMPLIFIER

Microphone **Body Frame Material Max Output**

Humidity Operating Range Frequency Range

Frequency Switch Plug-in Connector Power Source USB Charger Operation Time

50dB, multi-element, integrated

High Impact ABS

107 dB

At 20°C. 95% RH Low: 25Hz - 3.5kHz Medium: 100Hz - 18kHz High: 900Hz - 25kHz 3-position, user selectable Stereo Jack, 3.5mm diameter Two AA Ni-MH batteries (included) 110/240VAC, USB to Mini-B jack

Approx. 40 hours per charge

HEADPHONES (SE-HP)

Mylar, diameter 30mm. Diaphragm Impedance 32 ohms +/- 15% at 1kHz **Nominal Power** 4mW

Max Power 10mW

Sensitivity 100 dB S.P.L +/- 4dB 1kHz **Balance per Channel** +/- 3 dB at 1kHz **Frequency Response** 20Hz-20kHz

Stereo Plug, 3.5mm diameter **Plug-in Connector**

Cord Length 1200mm - +/-50mm Weight 50g +/-5g

Earpad Black, cushioned sponge

EARBUDS (LC-EB)

Diaphragm Mylar, diameter 10mm. 32 ohms +/- 15% at 1kHz **Impedance** 10mW **Max Power**

105 dB S.P.L +/- 3dB 1kHz Sensitivity +/- 3 dB at 1kHz **Balance per Channel**

20Hz-20kHz 1kHz **Frequency Response Plug-in Connector** Stereo Plug, 3.5mm diameter **Cord Length** 1150mm - +/-50mm

THD Less than 5% at 1kHz 0.126V Weight

15g + / - 5g



HS TARIFF CODE: 8515.50

SE9000HP DETAILS

WARRANTY MEASUREMENTS

3 year 3.05"x 2"x 0.75"

CERTIFIED CE & ROHS COMPLIANT CMS, MDS, ADA,

ACA 1557, Prop 65

Cleaning Instructions Available

CUBE AND USB CABLE ARE INCLUDED

LIGHTWEIGHT, PREMIUM QUALITY STEREO HEADPHONES AND EARBUDS

SWITCH

BELT/POCKET CLIP INCLUDED **FREQUENCY**

TACTILE

ON/OFF VOLUME CONTROL

WHEEL



www.sonictechnology.com superear@sonictechnology.com

FAX 530-272-4257 | 1-800-247-5548 P.O. Box 539, Grass Valley, CA 95945